

DESCRIPTION	Credence ASL3000 RF tester			x
MODEL	ASL3000			x
MANUFACTURER	Credence			x
SPEED	2.4GHz or 2.8GHz			x
# OF PINS	64 PADS			x
CPU MEMORY	1 GB min			x
O/S VER	XP			x
TESTER SOFTWARE	VISUAL ATE			6.1.1
UTILITY	208V / 40A / 3 WIRES			x
Slot Configuration				
Slot	BOARD	Part #	Rev	
1	OVI-30	671-3032-02	A	x
2	OVI-30	671-3032-03	A	x
3	OVI-30	671-3032-04	A	x
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15	DVI-2000	671-4676-05	A	x
16				
17	DVI-2000	671-4676-05	A	x
18				
19	OVI-30	671-3032-04	A	x
20	MUX-LV	671-4682-00	A	x
21	DVI-2000	671-4676-05	A	x
22				
23	MDI	671-4534-08	A	x
24	MDI	671-4534-08	A	x
25	MDI	671-4534-08	A	x
26	MDI	671-4534-08	A	x
27	CLK4	672-6135-03	A	x
28				
29				
30				
31				
MVNA				
HP RFIQ	MVNA	672-6204-00		x

SOURCES				
RF1	Q06ATE or SMATE			x
RF2	Q06ATE or SMATE			x
RF3	Q06ATE or SMATE			x
LO	Q06ATE or SMATE			x
SOFTWARE REV				
MVNA	VNA SW version			2.3.6
MADS				2.1
SMIQ rev.				
G4 Receiver firmware				
RF PORTS (Port #)				
HPPM2	1	657-0563-02		x
HPPM or HPPM2	2,3,4,5,6,7,8			x
E-MUX				x